outdoor sound solution for 10000 people

No.	Name	Data	QTY	Unit	Price	Photo
1	Double 12 full frequency passive	Type: 2-channel full frequency linear array speaker Appearance: Black Composition: 12 "* 2+3" * 1+Horn Impedance: 4 Ω Average power: 800W Program power: 3200W Frequency response: 50Hz -20KHz (± 3dB) Sensitivity (1W/1M): 112dB Maximum sound pressure level: 139dB Diffusion angle: 100 º -7 º Product size: 960 * 360 * 410 Net weight: 38KG "	16	p	12545.45	
2	Double 18 inch bass passive	Type: Double 18 inch passive subwoofer Appearance: Black Composition: 18 "* 2 125 cores Impedance: 8 Ω Average power: 1600W Program power: 6400W Frequency response: 35Hz-300Hz (± 3dB) Sensitivity (1W/1M): 113dB Maximum sound pressure level: 136dB Product size: Net weight: KG "	8	p	5436.36	
3	Linear array hanger	Linear array hanger	2	p	261.36	
4	Single 15 professional listening speaker	Type: 2-way rotatable waveguide horn, multi angle projection full frequency speaker Composition: 15 "+2"+Horn Impedance: 8 Ω Average power: 500W Program power: 1000W Frequency response: 35Hz-20KHz Sensitivity (1W/1M): 101dB Maximum sound pressure level: 129dB Diffusion angle: 90 º -60 º Product size: 430 * 450 * 675 Net weight: 24.2kg	4	p	1219.70	 4只，4只依场地情况
5	digital amplifier	Stereo dual channel mode: 8 Ω 4 * 1000W 4 Ω 4 * 1650W, Bridge mono mode: 8 Ω 3300W THD<0.1% (10% of full power), IMD<0.05% (60Hz/7KHz), 10% of full power, Signal to noise ratio:>106dB, Conversion speed:>60V/us, Damping coefficient: > 600; 1 (8 Ω 100Hz), Frequency response: 20Hz+20KHz, Input sensitivity: 0.775V, 1V, 32dB, Input impedance: 10K Ω/20K Ω (unbalanced/balanced) Size: 483W × 430D × 44H (mm) Net weight: 9kg	1	p	618.56	
6	digital amplifier	Stereo dual channel mode: 8 Ω 4 * 1000W 4 Ω 4 * 1650W, Bridge mono mode: 8 Ω 3300W THD<0.1% (10% of full power), IMD<0.05% (60Hz/7KHz), 10% of full power, Signal to noise ratio:>106dB, Conversion speed:>60V/us, Damping coefficient: > 600; 1 (8 Ω 100Hz), Frequency response: 20Hz+20KHz, Input sensitivity: 0.775V, 1V, 32dB, Input impedance: 10K Ω/20K Ω (unbalanced/balanced) Size: 483W × 430D × 44H (mm) Net weight: 9kg	4	p	2648.48	

7	Transformer amplifier (3U)	8 ohms stereo power: 2x1800W 4 ohms stereo power: 2x2300W Frequency response: 20Hz-20KHz ± 0.5% Conversion rate: 30V/ μ S Total harmonic distortion (20Hz-20KHz):<0.05% Damping coefficient:>280 Signal to noise ratio ≥ 102dB Input sensitivity 1Vrms Input impedance 20k Ω balanced/10K Ω unbalanced Input interface 2 x XLR Output interface 2 x NL4 Circuit form: CLASSH+BT Voltage~110V/~220V, 50Hz/60Hz Product dimensions (W x H x D) 480mm x 132mm x 548mm Packaging size (1 unit/pack) 605mm x 190mm x 560mm Product net weight 33kg Product gross weight (1 unit/pack) 35.5kg "	4	p	2509.09	
8	4 in 8 out processors	Input 3 channels, maximum gain+20dBu Output 6 channels, maximum gain+20dBu Output impedance 600 ohms Dynamic range>108dBu, frequency response 22Hz-22KHz Frequency response<± 0.25dBu, 15Hz-20KHz Intermodulation distortion<0.01%, 20Hz-20KHz @+10dBu balance input Sampling rate 96KHZ Signal to noise ratio>100dBu, 20Hz-20KHz Analog to Digital Converter 24 bit input and output Low pass/high pass filter 12.18.24 or 48dB/octave Parameter equalizer Band width from 0.05 to 3 octaves, frequency from 20Hz to 20KHz, gain ± 20dB step 0.1dB Delay 0-2000ms Delay step distance of 21us Main menu key parameter menu exit enter input A.B mute, edit and output channHL control LCD screen 2 × 20 LED screen Input LED 0.. -6. -12. -18. -24. and limit Output LED 0.. -6. -12. -18. -24. and limit Product size HWD (mm) 45 × four hundred and eighty-three × two hundred and forty Power supply 50/60Hz, 90V-240V AC power<20W Net weight/gross weight (kg) 2.8/3.5 "	2	p	975.76	
9	8-way sequencer	"Standard 19 inch chassis, 1U exterior design, 220V 45A LED high-precision voltage display meter, 8 independent power switches, universal socket output, maximum output of 16A per channel, total input current of 32A.", Front 1 backup direct power supply output, output current of 7A, built-in intermittent delay of 1.5S, Input power supply: AC220V 50Hz, Unlimited extreme connection, Size: 483 × two hundred and sixty × 44mm "	2	p	278.79	
10	Power amplifier cabinet	16U fireproof and shockproof without door	2	p	226.52	
11	flightcase	Full frequency 1 in 2, low frequency 1 in 1	8	p	1045.45	
12	flightcase	Bass 1 in 1	8	p	1045.45	
13	wire rod	cable	0	m	0.00	
14	wire rod	Signal passing line	0	p	0.00	
total					28810.98	